

Subaccount is set to 8540G-00058CPA

File 351:Derwent WPI 1963-2001/UD,UM &UP=200212  
(c) 2002 Derwent Info Ltd

```

      Set  Items  Description
      ---  -
?s pn=(jp 3167752 or jp 91167752)
           2  PN=JP 3167752
           0  PN=JP 91167752
      S1      2  PN=(JP 3167752 OR JP 91167752)
?s s1 and pd=19910703
           2  S1
           3445 PD=19910703
      S2      0  S1 AND PD=19910703

?s s1 and py=1991
           2  S1
           559867 PY=1991
      S4      1  S1 AND PY=1991
?t s4/7/all

```

4/7/1

DIALOG(R)File 351:Derwent WPI  
(c) 2002 Derwent Info Ltd. All rts. reserv.

008752902 \*\*Image available\*\*

WPI Acc No: 1991-256918/ 199135

**Gas-diffusing electrode for solid-electrolyte fuel battery - consists of  
gas-diffusing film bonded to rugged-surface electrolyte-reactive film**

Patent Assignee: MITSUBISHI HEAVY IND CO LTD (MITO )

Number of Countries: 001 Number of Patents: 002

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 3167752	A	19910719	JP 89306556	A	19891128	199135 B
JP 2831061	B2	19981202	JP 89306556	A	19891128	199902

Priority Applications (No Type Date): JP 89306556 A 19891128

Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
JP 3167752	A		5		
JP 2831061	B2		4	H01M-004/86	Previous Publ. patent JP 3167752

\* Abstract (Basic): JP 3167752 A

Electron gun pref. used for chemical reaction process within medium deg. of vacuum atmos. having electron feeding element conducting photo or thermo-electron radiation, has inert gas feeder to maintain electron radiating portion of element in inert gas atmos.

ADVANTAGE - Long term stabilised radiating condition is obtd. for electron gun.

Dwg.1/2

JP 2831061 B

Electron gun pref. used for chemical reaction process within medium deg. of vacuum atmos. having electron feeding element conducting photo or thermo-electron radiation, has inert gas feeder to maintain electron radiating portion of element in inert gas atmos.

ADVANTAGE - Long term stabilised radiating condition is obtd. for electron gun.

Derwent Class: L03; X16

International Patent Class (Main): H01M-004/86

International Patent Class (Additional): H01M-008/02; H01M-008/10

?logoff